



FREE MATCH



LOW-STATIC DUCT TYPE INDOOR UNIT

Model: TM12HFDI



Item	Unit	Specification
Model	—	TM12HFDI
System and Electrical Ratings		
Cooling Capacity	Btu/h	11900
Heating Capacity	Btu/h	13100
Sound Pressure (High/Low)	dB(A)	39/32
Air Flow (max)	CFM	323.675
Ext Static Pressure (max/min)	InWg	0.04/0.03
Normal Operational Voltage	—	208-230 V, 1 Ph, 60 Hz
Voltage Range	V	187-253
Power Cable Size	—	AWG18(0.82)
Unit and Pipe Data		
Communication Cable Wire Size	—	AWG18-4
Unit Dimensions (L×H×D)	Inch	27.6 x 24.2 x 7.9
Weight (Net)	lbs	50.715
Weight (Gross)	lbs	63.945
Drain Connection	inch	1
Refrigerant Type	—	R410A
Gas Pipe Size	Inch	3/8
Liquid Pipe Size	Inch	1/4
Connection Method	—	Flare Connection




Job Name:		Date:	
Reference #:			
Signature:			

TOSOT NORTH AMERICA
 930 W 21ST STREET, CHICAGO IL 60608
 TEL: +1(312)800-8455
 EMAIL: SALES@TOSOT-NA.COM




FREE MATCH

OUTLINE AND PHYSICAL DIMENSIONS



	A	B	C	D	E	F	G	H	I	J
TM12HFDI	742	491	662	620	700	615	782	156	200	635



Liquid Line Valve	1/4-in OD Flared
Gas Line Valve	3/8-in OD Flared
Net Weight ODU	50.715 lb
Gross Weight ODU	63.945 lb

Unit: mm(inch)